

EDMDG 20/150

HAFNER

Megvezetett kompakt henger - golyócsapágyas - állítható véghelyzet-csillapítással



productDataPdf.propertiesHeader

Csatlakozás	G 1/8"
Közeg	sűrített levegő
Húzóerő (6 bar)	150 N
Dugattyú	mágneses
Tömítés anyaga	NBR
Átmérő	Ø20
Hőmérséklet tartomány	-20°C...+80°C
Hengertest anyaga	eloxált alumínium
Dugattyú anyaga	alumínium
Vezetőpersely anyaga	szinterbronz
Dugattyúrúd átmérő	Ø10 mm
Lökethossz	150 mm
Üzemi nyomás	1...10 bar
Nyomóerő (6 bar)	179 N
Lökétség csillapítás	állítható
Dugattyúrúd anyaga	keménykrómozott acél (CK45)
Funkció	kettős működésű

HAFNER

Technical drawing of a T-shaped bracket, showing various views and dimensions:

- Top View (DET. F):** Dimensions include 3.3, 3.3, 6.6, 3.3, and 6.6.
- Side View (DET. C):** Dimensions include 4 x MM, J, K, G, H, H_C, H_B, H_A, V_A, V_B, V_C, 2 x P, and XA.
- Front View (DET. D):** Dimensions include Z, WA, XA, WB, X, J, J, ML, X, U, E, A+, B+, C+, PA+, GA, GB, 2 x P, and XA.
- End View (DET. E):** Dimensions include S, Q, T, R, and XA.
- Detail View (DET. F):** Dimensions include 3.3, 3.3, 6.6, 3.3, and 6.6.
- Detail View (DET. C):** Dimensions include 4 x MM, J, K, G, H, H_C, H_B, H_A, V_A, V_B, V_C, 2 x P, and XA.
- Detail View (DET. D):** Dimensions include Z, WA, XA, WB, X, J, J, ML, X, U, E, A+, B+, C+, PA+, GA, GB, 2 x P, and XA.
- Detail View (DET. E):** Dimensions include S, Q, T, R, and XA.

<https://hafner-pneumatika.com>

Q	18	26	30	30	40	50
R	70	78	96	104	130	130
S	30	40	45	45	60	70
T	81	91	110	118	146	158
U	54	64	78	86	110	124
VA	72	82	98	106	130	142
VB	44	50	63	72	92	110
VC	12,5	15	19,5	25	33	34
WA (löket: 0-75)	44	44	48	48	48	52
WA (löket: 100-175)	120	120	124	124	124	128
WA (löket: 200)	200	200	200	200	200	200
WB (löket: 0-75)	39	39	45	46	48	50
WB (löket: 100-175)	77	77	83	84	86	88
WB (löket: 200)	117	117	121	122	124	124
X ±0,02	28	34	42	50	66	80
Ø XA H9	3	4	4	4	5	5
XB	3,5	4,5	4,5	4,5	6	6
XC	3	3	3	3	4	4
XL	6	6	6	6	8	8
YY	M6	M6	M8	M8	M10	M10
YL	12	12	16	16	20	22
Z	17	17	21	22	24	24
a	5,4	5,4	6,5	6,5	8,5	11
b	8,4	8,4	10,5	10,5	13,5	17,8
c	4,5	4,5	5,5	5,5	7,5	10
d	3,6	3,8	4,5	5	5,5	8
e	8,6	9	10,5	10,5	14,5	19,5